




LP110WH3K **WARM**

LP110WH4K **COOL**



Lumi-Plugin® Downlight

Downlight designed to suit every room in the home.



LUMI-PLUGIN®

Lumi-Plugin® Range.

Lumi-Plugin® Downlight Spec.

Lumi-Plugin® Downlight Features.


Uniquely beautiful Downlight

Lumi-Plugin® Downlight Features.


Designed to suit every room our Downlight provides beautiful, modern and stylish lighting – guaranteed for five years. Our range of interchangeable plugins simply click into place at the centre of our Downlight to create spaces that can be safe and streamlined.



Mains
powered




100°
beam angle




600
lumens



Fire-rated
30/60/90




IP65
rated




Class 2

Find all the information you need
to achieve streamlined results here. >



Uniquely beautiful Downlight _____


Lumi-Plugin® Downlight Spec.



Lumens	600 lumens		
Wattage	8.2W		
Voltage	220-240V AC 50Hz		
Dimmable	Trailing edge		
Built-in driver	Yes		
Colour temperature	3000K / 4000K		
Guarantee / hours	5 years / 50,000 hours		
Colour rendering index (CRI)	>80		
Beam angle	100 degrees		
kWh per 1000 hour life	10kWh		
Luminaire efficiency	86.05lm/W		
Energy rating	F		
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist		
Product colour	White		
Dimensions	Cut-out size	92mm	Diameter 110mm
	Height	60.7mm	Depth 55mm

Non fire-rated and non IP rated models available
LP110WH3KIP / LP110WH4KIP
LP110WH3KFR / LP110WH4KFR
LP110WH3KNIL / LP100WH4KNIL

Find all the information you need to achieve streamlined results here. >




Lumi-Plugin® Range.

Reimagine lighting. _____

Lumi-Plugin[®] Range.

View our range of interchangeable
and easy-to-install plugins. >



Lumi-Plugin[®]
Downlight



Lumi-Smoke[®]



Lumi-Heat[®]



Lumi-CO[®]



Lumi-Sprinkler[®]



Lumi-Mist[®]



Lumi-Emergency[®]




Lumi-PIR[®]



One-Smoke[®]



One-Heat[®]



LUMI-PLUGIN[®]

+44 (0) 3303 801 329
hello@lumi-plugin.com
lumi-plugin.com

