




LP110WH3KMBWHA WARM

LP110WH4KMBWHA COOL



Lumi-Heat[®]

Downlight integrated with world's smallest mains heat alarm.



LUMI-PLUGIN[®]

Lumi-Heat[®] Features.

Lumi-Heat[®] Spec.

Lumi-Plugin[®] Downlight.

Lumi-Plugin[®] Range.

World's smallest mains heat alarm

Lumi-Heat[®] Features.

Seriously small for a serious job because we think heat alarms should be discreet and complete. Designed to click inside our Downlight, it connects wirelessly to our Lumi-Smoke[®], One-Smoke[®] and One-Heat[®] alarms to protect the entire property.



Mains powered



10-year sealed battery



Wireless connectivity



Fire-rated
30/60/90




Pre-wired junction box



Class 2

Find all the information you need to achieve streamlined results here. >




Lumi-Heat[®] Spec.

Lumi-Plug-in[®] Downlight.

Lumi-Plug-in[®] Range.


World's smallest mains heat alarm

Lumi-Heat[®] Spec.



Voltage	110V AC, 230V DC			
Battery type	Non-replaceable CR2 10-year battery			
Interlink frequency	868MHz			
Operating humidity	-10°C to + 70°C			
Power consumption	145mAh in non-alarm condition			
Sound	Audible indicator minimum 85dB @ 3 metres in anechoic successive tones			
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist			
Complies to	BS 5839: Part 6 Grade D1			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height	116mm	Depth	92mm

Find all the information you need to achieve streamlined results here. >




KM 755618
BS 5446-2:2003
A1 3201-001

Integrated with _____

Lumi-Plugin[®] Downlight.

Designed to fit in every room and fit every plugin seamlessly. Our Downlight provides beautiful, sophisticated and contemporary lighting – guaranteed for 5 years. All plugins are reliable, compatible, and interchangeable to create streamlined ceilings and stylish interiors.



Lumens	600 lumens
Wattage	8.2W
Voltage	220-240V AC 50Hz
Dimmable	Trailing edge
Built-in driver	Yes
Colour temperature	3000K / 4000K
Guarantee / hours	5 years / 50,000 hours
Colour rendering index (CRI)	>80
Beam angle	100 degrees
kWh per 1000 hour life	10kWh
Luminaire efficiency	86.05lm/W
Energy rating	F
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist
Product colour	White



Reimagine lighting.

Lumi-Plugin[®] Range.

View our range of interchangeable and easy-to-install plugins. [>](#)



Lumi-Plugin[®]
Downlight



Lumi-Smoke[®]



Lumi-Heat[®]



Lumi-CO[®]



Lumi-Sprinkler[®]



Lumi-Mist[®]



Lumi-Emergency[®]



Lumi-PIR[®]



One-Smoke[®]



One-Heat[®]



LUMI-PLUGIN[®]

+44 (0) 3303 801 329
hello@lumi-plugin.com
lumi-plugin.com

