




LP110WH3KSPK WARM

LP110WH4KSPK COOL



Lumi-Sprinkler®

Downlight integrated with concealed sprinkler head.



LUMI-PLUGIN®

Lumi-Plugin® Range.
Lumi-Plugin® Downlight.
Lumi-Sprinkler® Spec.
Lumi-Sprinkler® Features.

Concealed sprinkler head

Lumi-Sprinkler[®] Features.

Extinguish fires with our Lumi-Sprinkler[®] – it's like having your own firefighter in every room. In an emergency, a supply of water sprays out from the centre of our Downlight to suppress fire and allow everyone to evacuate to safety.


Concealed sprinkler head for discreet but complete protection.

Automatic system to take action at the second a fire starts.

Contains the fire to a specific area until full extinguish can take place.

Reduces fire damage to the home as much as possible.

Find all the information you need to achieve streamlined results here. >




Lumi-Sprinkler[®] Spec.

Lumi-Plugin[®] Downlight.

Lumi-Plugin[®] Range.


Concealed sprinkler head

Lumi-Sprinkler[®] Spec.



Brand	RD107	RD205		
K factor	5.6	4.9		
Cover plate size	60mm (2-3/8")			
Link	Fusible link			
Max. working pressure	12.1 bar (175 psi)			
Temperature rating	Sprinkler: 72°C (162°F) Cover plate: 60°C (140°F)			
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist			
Vertical adjustment	9.0mm (3/8")			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height (excluding pipework)	66mm	Depth (excluding pipework)	55mm

Find all the information you need to achieve streamlined results here. >




Integrated with _____

Lumi-Plugin[®] Downlight.



Designed to fit in every room and fit every plugin seamlessly. Our Downlight provides beautiful, sophisticated and contemporary lighting – guaranteed for 5 years. All plugins are reliable, compatible, and interchangeable to create streamlined ceilings and stylish interiors.


Lumens	600 lumens
Wattage	8.2W
Voltage	220-240V AC 50Hz
Dimmable	Trailing edge
Built-in driver	Yes
Colour temperature	3000K / 4000K
Guarantee / hours	5 years / 50,000 hours
Colour rendering index (CRI)	>80
Beam angle	100 degrees
kWh per 1000 hour life	10kWh
Luminaire efficiency	86.05lm/W
Energy rating	F
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist
Product colour	White



Reimagine lighting.

Lumi-Plugin[®] Range.

View our range of interchangeable and easy-to-install plugins. [>](#)



Lumi-Plugin[®]
Downlight



Lumi-Smoke[®]



Lumi-Heat[®]



Lumi-CO[®]



Lumi-Sprinkler[®]



Lumi-Mist[®]



Lumi-Emergency[®]




Lumi-PIR[®]



One-Smoke[®]



One-Heat[®]



LUMI-PLUGIN[®]

+44 (0) 3303 801 329
hello@lumi-plugin.com
lumi-plugin.com

