




Lumi-Emergency[®]

Downlight integrated with emergency lighting.



LUMI-PLUGIN[®]

- Lumi-Plugin[®] Range.
- Lumi-Plugin[®] Downlight.
- Lumi-Emergency[®] Living Spec.
- Lumi-Emergency[®] Living Features.
- Lumi-Emergency[®] Corridor Spec.
- Lumi-Emergency[®] Corridor Features.
- Lumi-Emergency[®] Flood Spec.
- Lumi-Emergency[®] Flood Features.

Flood lights that put safety in the spotlight

LP110WH3KFLEM WARM
LP110WH4KFLEM COOL

Lumi-Emergency[®] Flood Features.

Lumi-Emergency[®] Flood plugins switch on in an emergency to ensure all exit routes are well lit. They are best positioned above fire extinguishers, near fire doors, and on stairways.



Mains
powered



Battery
back-up



Fire-rated
30/60/90



Pre-wired
junction box

Find all the information you need
to achieve streamlined results here. >




Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Emergency[®] Living Spec.
Lumi-Emergency[®] Living Features.
Lumi-Emergency[®] Corridor Spec.
Lumi-Emergency[®] Corridor Features.
Lumi-Emergency[®] Flood Spec.

Flood lights that put safety in the spotlight

LP110WH3KFLEM WARM
LP110WH4KFLEM COOL


Lumi-Emergency[®] Flood Spec.



Battery size / type	3.2V 3.8Ah LiFePO4			
Beam angle	115 degrees			
Voltage	240V			
Light source	Samsung LH315B			
Colour temperature	6500K			
Non-maintained	Yes			
Output at 550mA	201 lumens			
Power rating	3W			
Wiring method	Series connection via C4201 plug			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height	67.5mm	Depth	55mm

Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Emergency[®] Living Spec.
Lumi-Emergency[®] Living Features.
Lumi-Emergency[®] Corridor Spec.
Lumi-Emergency[®] Corridor Features.

Find all the information you need
to achieve streamlined results here. >



Lighting every corridor for a safe exit

LP110WH3KCOEM WARM
LP110WH4KCOEM COOL

Lumi-Emergency[®] Corridor Features.

Long lasting. Far reaching. The horizontal beam angle of our Lumi-Emergency[®] Corridor plugin can light up the length of corridors and hallways to create safer exit routes.



Mains powered



Battery back-up




Fire-rated
30/60/90



Pre-wired
junction box

Find all the information you need to achieve streamlined results here. >




Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Emergency[®] Living Spec.
Lumi-Emergency[®] Living Features.
Lumi-Emergency[®] Corridor Spec.

Lighting every corridor for a safe exit


LP110WH3KCOEM WARM
LP110WH4KCOEM COOL

Lumi-Emergency[®] Corridor Spec.



Battery size / type	3.2V 3.8Ah LiFePO4			
Beam angle	155 x 115 degrees			
Voltage	240V			
Light source	Samsung LH315B			
Colour temperature	6500K			
Non-maintained	Yes			
Output at 550mA	232 lumens			
Power rating	3W			
Wiring method	Series connection via C4201 plug			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height	72.3mm	Depth	55mm

Find all the information you need to achieve streamlined results here. >



Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Emergency[®] Living Spec.
Lumi-Emergency[®] Living Features.

Emergency lights for safe and sound living

LP110WH3KHTEM WARM
LP110WH4KHTEM COOL

Lumi-Emergency[®] Living Features.

For restful rooms, emergency protection with its own 'do not disturb' design. Highly considered and considerate, our Lumi-Emergency[®] Living plugin is engineered to dim its green LEDs at night for peace of mind and restful sleep.



Mains powered



Battery back-up



Fire-rated
30/60/90



Pre-wired
junction box

Find all the information you need to achieve streamlined results here. >




Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Emergency[®] Living Spec.

Emergency lights for safe and sound living

LP110WH3KHTEM WARM
LP110WH4KHTEM COOL

Lumi-Emergency[®] Living Spec.

Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.



Battery size / type	3.2V 3.8Ah LiFePO4			
Beam angle	135 degrees			
Voltage	240V			
Light source	Samsung LH315B			
Colour temperature	6500K			
Non-maintained	Yes			
Output at 550mA	232 lumens			
Power rating	3W			
Wiring method	Series connection via C4201 plug			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height	71.8mm	Depth	55mm

Find all the information you need to achieve streamlined results here. >




Integrated with _____

Lumi-Plugin[®] Downlight.

Designed to fit in every room and fit every plugin seamlessly. Our Downlight provides beautiful, sophisticated and contemporary lighting – guaranteed for 5 years. All plugins are reliable, compatible, and interchangeable to create streamlined ceilings and stylish interiors.



Lumens	600 lumens
Wattage	8.2W
Voltage	220-240V AC 50Hz
Dimmable	Trailing edge
Built-in driver	Yes
Colour temperature	3000K / 4000K
Guarantee / hours	5 years / 50,000 hours
Colour rendering index (CRI)	>80
Beam angle	100 degrees
kWh per 1000 hour life	10kWh
Luminaire efficiency	86.05lm/W
Energy rating	F
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist
Product colour	White



Reimagine lighting.

Lumi-Plugin® Range.

View our range of interchangeable and easy-to-install plugins. >



Lumi-Plugin®
Downlight



Lumi-Smoke®



Lumi-Heat®



Lumi-CO®



Lumi-Sprinkler®



Lumi-Mist®



Lumi-Emergency®



Lumi-PIR®



One-Smoke®



One-Heat®



LUMI-PLUGIN®

+44 (0) 3303 801 329
hello@lumi-plugin.com
lumi-plugin.com

