




LP110WH3KIMIST WARM

LP110WH4KIMIST COOL



Lumi-Mist[®]

Downlight integrated with iMist.



LUMI-PLUGIN[®]

Lumi-Plugin[®] Range.
Lumi-Plugin[®] Downlight.
Lumi-Mist[®] Spec.
Lumi-Mist[®] Features.

Mist fire suppression

Lumi-Mist[®] Features.

Engineered to save lives and use less water. Designed to offer the protection of traditional sprinkler systems without needing to install a water tank.


Damage control is under control with even less water used.

No tanks required with mist suppression so space can be saved.

Quicker installation with flexible hoses avoiding large sprinkler pipework.

80% less water used compared to traditional sprinkler systems.

Find all the information you need to achieve streamlined results here. >




Lumi-Mist[®] Spec.

Lumi-Plugin[®] Downlight.

Lumi-Plugin[®] Range.

Mist fire suppression

Lumi-Mist[®] Spec.



Design pressure	36+Bar			
Design flow	8lts (max)			
Coverage	16m ² (max) floor area per nozzle			
Temperature rating	55 degrees +			
Approval	Successfully live fire tested to BS 8458:2015 Annex C by Exova Warringtonfire and ongoing R&D testing by FPA.			
Sound	Audible indicator minimum 85dB @ 3 metres in anechoic successive tones			
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist			
Classification	Residential			
Product colour	White			
Dimensions	Cut-out size	92mm	Diameter	110mm
	Height	81mm	Depth	55mm


Find all the information you need to achieve streamlined results here. >




Integrated with _____

Lumi-Plugin® Downlight.

Designed to fit in every room and fit every plugin seamlessly. Our Downlight provides beautiful, sophisticated and contemporary lighting – guaranteed for 5 years. All plugins are reliable, compatible, and interchangeable to create streamlined ceilings and stylish interiors.



Lumens	600 lumens
Wattage	8.2W
Voltage	220-240V AC 50Hz
Dimmable	Trailing edge
Built-in driver	Yes
Colour temperature	3000K / 4000K
Guarantee / hours	5 years / 50,000 hours
Colour rendering index (CRI)	>80
Beam angle	100 degrees
kWh per 1000 hour life	10kWh
Luminaire efficiency	86.05lm/W
Energy rating	F
Fire-rated	30/60/90 – Solid Joist 30 – Metal Webbed Joist & I-Joist
Product colour	White



Reimagine lighting.

Lumi-Plugin[®] Range.

View our range of interchangeable and easy-to-install plugins. [>](#)



Lumi-Plugin[®]
Downlight



Lumi-Smoke[®]



Lumi-Heat[®]



Lumi-CO[®]



Lumi-Sprinkler[®]



Lumi-Mist[®]



Lumi-Emergency[®]



Lumi-PIR[®]



One-Smoke[®]



One-Heat[®]



LUMI-PLUGIN[®]

+44 (0) 3303 801 329
hello@lumi-plugin.com
lumi-plugin.com

