



VKKW.EX15652
Residential Automatic Sprinklers

Page Bottom

Residential Automatic Sprinklers

[See General Information for Residential Automatic Sprinklers](#)

RAPIDROP GLOBAL LTD

EX15652

RUTLAND BUSINESS PARK

NEWARK RD

PETERBOROUGH, PE1 5WA UNITED KINGDOM

Flush pendent, Concealed Pendent, Flush horizontal sidewall sprinklers for wet systems only with a maximum pressure of 175 psig Models RD201, RD203, RD205, RD206, RD207 and RD208 sprinklers are chrome plated, white, dark brown, brass or black paint coated.

SIN/Type	Max Coverage Area		Min Flow Rate GPM/ Sprinkler	Min Pressure (psig)	K-Factor	Temp Rating, °F
	Ft					
	Width	Length				
RD201	14	14	13	9.6	4.2	162
Flush						
Pendent						
RD201	16	16	14	11.1	4.2	162
Flush						
Pendent						
RD201	18	18	18	18.4	4.2	162
Flush						
Pendent						
RD201	20	20	22	27.4	4.2	162
Flush						
Pendent						
RD205/ #	12	12	13	7.0	4.9	162
Concealed Pendent						
RD205/ #	14	14	14	8.2	4.9	162
Concealed Pendent						
RD205/ #	16	16	15	9.4	4.9	162
Concealed Pendent						
RD205/ #	18	18	19	15	4.9	162
Concealed Pendent						
RD203/*	12	12	13	9.6	4.2	162
Flush Horizontal Sidewall						
RD203/*	14	14	16	14.5	4.2	162
Flush Horizontal Sidewall						
RD203/*	16	16	20	22.7	4.2	162
Flush Horizontal Sidewall						
RD203/*	12	12	20	12.7	5.6	162

Flush Horizontal Sidewall						
RD203/*	14	14	25	19.9	5.6	162
Flush Horizontal Sidewall						
RD203/*	16	16	29	26.8	5.6	162
Flush Horizontal Sidewall						
RD206/ #	16	16	13	7.0	4.9	162
Concealed Pendant						
RD206/ #	18	18	18	13.5	4.9	162
Concealed Pendant						
RD206/ #	20	20	21	18.4	4.9	162
Concealed Pendant						
RD206/ ##	12	12	13	7.0	4.9	175
Concealed Pendant						
RD206/ ##	16	16	14	8.2	4.9	175
Concealed Pendant						
RD207#, Flush Pendant	12	12	9	7.0	3.0	162
RD207#, Flush Pendant	14	14	11	13.4	3.0	162
Concealed Pendant						
RD208/ #	16	16	13	7.0	4.9	162
Concealed Pendant						
RD208/ #	18	18	17	12.0	4.9	162
Concealed Pendant						
RD208/ #	20	20	21	18.4	4.9	162
Concealed Pendant						
RD208/ ##	14	14	13	7.0	4.9	175
Concealed Pendant						
RD208/ ##	16	16	14	8.2	4.9	175
Concealed Pendant						
RD208/ ##	18	18	18	13.5	4.9	175

* - For installation 4 to 6 in. below ceiling.

- Utilizes 140 °F temperature rated flat coverplate.

- Utilizes 162 °F temperature rated flat coverplate

Last Updated on 2016-05-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".